

 **LIVEY**<sup>TM</sup>


EMBRACE  
THE FUTURE  
CONNECT

SPLENDOR  
**LT-800  
SERIES**

Luxurious Comfort | High Reliability | ENC Mic | Affordable Price

LIVEY Technologies LLC, USA  
Copyright 2024, All Rights Reserved.



 [hello@liveytech.com](mailto:hello@liveytech.com)  
 [www.liveytech.com](http://www.liveytech.com)

# GREAT SOUND BEST QUALITY



LT-800DM



LT-805DM-ENC



LT-800DP

## Technical Specifications

|                          |                            |  |                           |
|--------------------------|----------------------------|--|---------------------------|
| Audio Performance        | Connector Type             | QD (LT-800DP) USB-A (LT-800DM & LT-805DM)  |                           |
|                          | Speaker Size               | Φ28  |                           |
|                          | Speaker Max Input Power    | 50mW   |                           |
|                          | Speaker Sensitivity        | 105±3dB  |                           |
|                          | Speaker Frequency Range    | 100Hz~6.8KHz   |                           |
|                          | Microphone Directionality  | Noise-canceling Cardioid (LT-800DP & LT-800DM)<br>ENC Dual Mic Array Omni-Directional (LT-805DM) |                           |
|                          | Microphone Sensitivity     | -40±3dB@1KHz   |                           |
|                          | Microphone Frequency Range | 100Hz~3.4KHz   |                           |
|                          | Call Control               | Call answer/end, Mute, Volume +/-  | Yes (LT-800DM & LT-805DM) |
|                          |                            | Wearing  | Wearing Style             |
| Mic Boom Rotatable Angle | 320°                       |  |                           |
| Headband/Ear Cushion     | Foam                       |  |                           |
| Connectivity             | Connects to                | Desk phone (All)<br>PC Soft Phone (LT-800DM & LT-805DM)  |                           |
|                          | Hearing Protection         | 118dBA SPL   |                           |
| General                  | Cable Length               | 120cm (LT-800DP)<br>210cm (LT-800DM & LT-805DM)  |                           |
|                          | Package Content            | QD Headset & User Manual (LT-800DP)<br>USB Headset User Manual (LT-800DM & LT-805DM)             |                           |
|                          | Outer-Carton Size          | 190*155*40mm   |                           |
|                          | Weight w/ Cable            | 85g (LT-800DP)<br>115g (LT-800DM & LT-805DM)   |                           |
|                          | Working Temperature        | -5°C~45°C  |                           |
|                          | Warranty                   | 2 Years  |                           |
|                          | Certifications             |  |                           |

### Built with AI Noise Cancelling

LT800 Series Dual Microphone array with precise positioning, use advanced near-end talk SVC wide band built with Ai Noise cancellation technology, which can reduce up to 99% (maximum 40dB ) noise.

### Superior HD Sound Quality

Wideband technology speakers let you have lifelike, vibrant conversations and reduce listening fatigue

### High Reliability

Metal parts are used in key parts to maximize durability. Use tensile fiber cable to ensure the long life span of the headset.

### Built in with Ear Protection Feature

