

CONFERENCE SPEAKERPHONE 716CS



CONFERENCE SPEAKERPHONE LT-716 CS



Features

- AI –embedded noise cancelling.
- 4× High-performance MEMS microphones.
- ANS (Automatic Noise Suppression) effectively removes unwanted background noise for crystal clear and distortion-free voice.
- AEC (Acoustic Echo Cancellation) significantly reduces echo, ensure high-quality & natural-sounding communication.
- AGC (Automatic Gain Control) automatically adjusts the loudness to ensure all participants within a comfortable listening range.
- Dual-core HiFi 4 DSP, dramatically improves the quality of voice communication and audio experience.
- Advanced Bluetooth V5.3 offers faster & better connections, and backward compatibility.
- Wireless connection: connect to smartphone or tablet via Bluetooth.
- Wired connection: connect to PC or Mac with a USB-C cable.
- Built-in 1500mAh rechargeable Li-ion battery, offers you up to 8 hours talk time.
- Full-duplex Communication, allows data to be transmitted simultaneously in both directions, speak whenever you want, no need to wait for the other person to stop talking!

LIVEY LT-716CS

Specifications

Microphone

Polar Pattern	Digital output Omni-directional
Type	MEMS
Frequency Response	20Hz-20kHz
Sensitivity	-38dB +/-1dB
Signal to Noise Ratio	64.5dB A weighted
Pickup Range	3-5 meters

Speaker

Rated Power	3W
Driver Size	50mm (2 inch)
S.P. Level	100dB +/-3dB (0.1W/0.1M)
Impedance	4Ω
Frequency Range	100 Hz ~ 20KHz

Other

Bluetooth	Version 5.3+ BR + EDR + BLE
Chipset	ATS 2835
Bluetooth Range	10M
Connector	USB-C
OS Compatibility (USB)	Windows, MacOS, Chrome OS
Built-in Battery	3.7V/ 1500mAh Li-ion battery
Material	ABS + Plastic
Dimensions	12.5 (Dia) × 43.5cm (H)
Cable length	1.5M
Operating Temperature	0°C to 55°C (32° F to 131°F)
Storage Temperature	-25°C to 70°C (-13° F to 158°F)

