



Audixa Series

LIVEY AUDIXA 800 SERIES WIRED HEADSET

Designed to deliver exceptional sound performance while ensuring all-day comfort with AI noise reduction.





FOR OFFICE & ENTERPRISES, CONTACT CENTER, HOME OFFICE

Powerful Sound, Crystal-Clear Voice: Immerse yourself in unrivalled audio excellence with our headset's premium microphones and speakers, your gateway to seamless communication.



Compatible



KEY FEATURES

- Built with AI Noise Cancelling Dual-Mic Array with Omni-Directional mics
- Superior HD Sound Quality
- USB-A / QD Options
- Compatible with UC & Microsoft Teams
- Luxurious Comfort
- Top-level Acoustics & Hearing Protection

Variants



LT-800DM



LT-805DM-ENC



LT-800DP



**Crystal-Clear
Voice Calls**



**Immersive Audio
Experience**



**Seamless
Integration**

TECHNICAL SPECIFICATION

Model/Features		805DM-AINC	805M-AINC	800DP	800P
Audio Performance	Speaker Size	Ø28	Ø28	Ø28	Ø28
	Speaker Max Input Power				
	Speaker Sensitivity	105±3dB	105±3dB	105±3dB	105±3dB
	Speaker Frequency Range				
	Microphone	Noise-canceling Cardioid Directionality ENC Dual Mic Array Omni-Directional	Noise-canceling Cardioid Directionality ENC Dual Mic Array Omni-Directional	Noise-canceling Cardioid	Noise-canceling Cardioid
	Microphone Sensitivity				
	Microphone Frequency Range	100Hz~3.4KHz	100Hz~3.4KHz	100Hz~3.4KHz	100Hz~3.4KHz
Call Control	Call answer/end Mute, Volume +/-	Yes	Yes	Yes	Yes
Wearings	Wearing Style	Over-the-head	Over-the-head	Over-the-head	Over-the-head
	Mic Boom	Yes	Yes	Yes	Yes
	Rotatable Angle	320°	320°	320°	320°
	Headband/Ear Cushion	Foam	Foam	Foam	Foam
Connectivity	Connector Type	USB-A	USB-A	USB-A	USB-A
	Hearing Protection	yes	yes	yes	yes
General	Cable Length	1.2m (from In-line Controls unit to USB-A Plug)	1.2m (from In-line Controls unit to USB-A Plug)	1.2m (from In-line Controls unit to QD Plug)	1.2m (from In-line Controls unit to QD Plug)
	Outer-Carton Size	190mm*153mm*40mm	190mm*153mm*40mm	190mm*153mm*40mm	190mm*153mm*40mm
	Weight	112g	86g	112g	86g
	Operation Temperature	0°C to +45°C	0°C to +45°C	0°C to +45°C	0°C to +45°C
	Warranty	24 months	24 months	24 months	24 months